

Dell EMC D-PVM-OE-01

Dell Technologies PowerMax Operate

- Up to Date products, reliable and verified.
- Questions and Answers in PDF Format.

Full Version Features:

- 90 Days Free Updates
- 30 Days Money Back Guarantee
- Instant Download Once Purchased
- 24 Hours Live Chat Support

For More Information:

<https://www.testsexpert.com/>

- Product Version

Latest Version: 6.0

Question: 1

A systems administrator wants to attach a new IBM server to a PowerMax 8000. The administrator is concerned about the port flag setting and interoperability. Where can the correct port setting be retrieved?

Response:

- A. Live Optics
- B. Dell EMC E-Lab Navigator
- C. www.dell.com
- D. Unisphere Online Help

Answer: B

Question: 2

In a local configuration, where is Unisphere and Solutions Enabler installed?

Response:

- A. Host that has a direct connection to the Unisphere client
- B. Host that has a direct connection to the storage array
- C. In the guest operating system on the array
- D. In the tools guest on the array

Answer: B

Question: 3

How is the Allocated Capacity percentage for an SRP determined?

Response:

- A. Calculated against the total unsubscribed capacity
- B. Calculated against the used capacity
- C. Calculated against the overall capacity
- D. Calculated against the total subscribed capacity

Answer: C

Question: 4

How many DAEs are in a fully-populated PowerMax 8000?

Response:

- A. 8
- B. 16
- C. 12
- D. 20

Answer: C

Question: 5

You are in a meeting with a customer to discuss virtual provisioning on VMAX3 arrays. The customer wants information on extent allocation during thin device creation. How many extent(s) are allocated when a thin device is created?

Response:

- A. 0
- B. 1
- C. 12
- D. 42

Answer: A

Question: 6

A systems administrator wants to present Gatekeeper devices to two standalone Microsoft Windows servers that run Solutions Enabler control operations. What information should be provided to the administrator?

Response:

- A. Gatekeeper devices should be no larger than 6 KB in size
- B. Hosts that run Solutions Enabler do not require any Gatekeepers
- C. Gatekeeper devices can be shared across hosts
- D. Each host should have its own unique Gatekeepers

Answer: D

Question: 7

What is a requirement to initiate a non-disruptive migration?

Response:

- A. Host can see either the source or target array
- B. Until migration cutover, host must see the source array only
- C. Host must see both the source and target arrays
- D. Until migration cutover, host must see the target array only

Answer: C

Question: 8

Which SRDF/A feature keeps sessions active in the event of a temporary link loss?

Response:

- A. Multi-Cycle Mode
- B. Transmit Idle
- C. Write Folding
- D. Group-level Write Pacing

Answer: B

Question: 9

Which virtual servers can be discovered and managed using Unisphere for VMAX?

Response:

- A. VMware ESX/ESXi and Microsoft Hyper-V
- B. VMware ESX/ESXi and Citrix Xen
- C. VMware ESX/ESXi and Oracle Virtualization
- D. Microsoft Hyper-V and Red Hat Enterprise Virtualization

Answer: A

Question: 10

What can be used to relink a TimeFinder SnapVX target?

Response:

- A. Any snapshot of any source device
- B. Any generation of the same snapshot only
- C. Any snapshot of the same source device only
- D. Same generation of a snapshot only

Answer: C

For More Information – Visit link below:
<https://www.testsexpert.com/>

16\$ Discount Coupon: **9M2GK4NW**

Features:

■ Money Back Guarantee.....



■ 100% Course Coverage.....



■ 90 Days Free Updates.....



■ Instant Email Delivery after Order.....

